

[Twin Turbo Series](#)

TLHT-V88W-930-S



More Information



RoHS Compliant

Specifications

Mounting	Panel Mount with Volume Control
Color	White
Operating Mode	Stacatto Tone
Operating Voltage	9-30 Vdc
Operating Frequency	3000±250 Hz
Typical Operating Current	110 mA at 9 Vdc 50 mA at 30 Vdc
Typical Sound Pressure	85 ±5 dB(A) at 9 Vdc at 24 inches (61 cm), at 25°C 103 ±5 dB(A) at 30 Vdc at 24 inches (61 cm), at 25°C
Termination	Quick Connect Blades with Screws
Termination Strength	Pull test with a maximum of 22 pounds (10 kg) load
Operating Temperature	-20_C to +65_C
Storage Temperature	-40_C to +85_C
Surge Voltage	20% over maximum rated voltage for less than 5 minutes
Reverse Voltage Protection	To the maximum operating voltage
Construction Materials	Lens/Case- White Translucent Polycarbonate 94 VO Potting- 2 parts epoxy resin or silicone, black
Gasket	Gasket (Included) 0.125" thick, 60 Durometer Neoprene ASTM B117 Certified - Withstands exposure to salt spray for 300 hours IP 68 Certified - Withstands water submergence and dust exposure Humidity- 95% relative humidity at +40_C continuously for 100 hours. Vibration- Withstands vibration between 0 and 55 Hz. on all axes.
Life Expectancy	10 years under normal operating conditions.
Warranty	For a period of two years from the date of manufacture under normal operating conditions.
Notes	This product is not intended as a life safety device.
Terms and Conditions of Sale	Link here


Diagram of the rear wheel assembly showing the rear axle and brake components. The diagram includes a dimension line indicating a distance of 0.70m (17.8mm) between two points on the axle.

Diagram of a ring with dimensions: 0.31 in [7.9 mm] and 128 in [32.5 mm].


GASKET

GASKET

SIDE




FRONT



14 1/2 in
[368 mm]

FRONT



"S" TERMINALS

STAINLESS STEEL SCREWS
6 X 32 0.25 LONG
(6.4)

0.032
(0.81)

0.250
(6.4)

0.372
(7.9)

0.312
(7.9)

0.100
(4)

6/32 BREAD

"S" TERMINALS