

[CAN Alarm Series](#)

CANL-97G-930-H



**Specifications**

|                                     |   |
|-------------------------------------|---|
| <b>Mounting</b>                     | Panel Mount   |
| <b>Color</b>                        | Green   |
| <b>Operating Mode</b>               |   |
| <b>Operating Voltage</b>            | 9-30 Vdc  |
| <b>Typical Operating Current</b>    | 190 mA at 9 Vdc<br>55 mA at 30 Vdc  |
| <b>Typical Brightness</b>           | 1700 cd/m <sup>2</sup> , at 9 Vdc at 25°C<br>1850 cd/m <sup>2</sup> , at 30 Vdc at 25°C   |
| <b>Termination</b>                  | Deutsch DT04-4P (gold terminals)  |
| <b>Termination Strength</b>         | Pull test with a maximum of 22 pounds (10 kg) load  |
| <b>Operating Temperature</b>        | -20_C to +65_C  |
| <b>Storage Temperature</b>          | -40_C to +85_C  |
| <b>Surge Voltage</b>                | 20% over maximum rated voltage for less than 5 minutes  |
| <b>Reverse Voltage Protection</b>   | To the maximum operating voltage  |
| <b>Gasket</b>                       | Gasket 0.062" thick, 60 Durometer Neoprene<br>ASTM B117 Certified - Withstands exposure to salt spray for 300 hours<br>IP 68 Certified - Withstands water submergence and dust exposure |
| <b>Construction Materials</b>       | Humidity- 95% relative humidity at +40_C continuously for 100 hours.<br>Vibration- Withstands vibration between 0 and 55 Hz. on all axes.   |
| <b>Life Expectancy</b>              | 10 years under normal operating conditions.   |
| <b>Warranty</b>                     | For a period of two years from the date of manufacture under normal operating conditions.   |
| <b>Notes</b>                        | This product is not intended as a life safety device.   |
| <b>Terms and Conditions of Sale</b> | <a href="#">Link here</a>   |

More Information

 **RoHS** Rohs Compliant

 **CE** CE Compliant

Dimensions

BACK

SIDE

