




## Specifications

|                                     |                                                                                                                                                                                                                  |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Mounting</b>                     | Panel Mount with Volume Control                                                                                                                                                                                  |
| <b>Color</b>                        | Red                                                                                                                                                                                                              |
| <b>Operating Mode</b>               | Extra Loud Multiple Tone                                                                                                                                                                                         |
| <b>Operating Voltage</b>            | 9-30 Vdc                                                                                                                                                                                                         |
| <b>Operating Frequency</b>          | 3000±250 Hz                                                                                                                                                                                                      |
| <b>Typical Operating Current</b>    | 65 mA at 9 Vdc<br>130 mA at 30 Vdc                                                                                                                                                                               |
| <b>Typical Sound Pressure</b>       | 100 ±5 dB(A) at 9 Vdc at 24 inches (61 cm), at 25°C<br>108 ±5 dB(A) at 30 Vdc at 24 inches (61 cm), at 25°C                                                                                                      |
| <b>Termination</b>                  | Quick Connect Blades                                                                                                                                                                                             |
| <b>Termination Strength</b>         | Pull test with a maximum of 22 pounds (10 kg) load                                                                                                                                                               |
| <b>Operating Temperature</b>        | -20_C to +65_C                                                                                                                                                                                                   |
| <b>Storage Temperature</b>          | -40_C to +85_C                                                                                                                                                                                                   |
| <b>Surge Voltage</b>                | 20% over maximum rated voltage for less than 5 minutes                                                                                                                                                           |
| <b>Reverse Voltage Protection</b>   | To the maximum operating voltage                                                                                                                                                                                 |
| <b>Construction Materials</b>       | Case- Plastic _NORYL_ N-190, Flame Retardant UL 94-VO, Black<br>Internal Circuit- Audio-oscillator and piezoelectric driver<br>Potting- 2 parts epoxy resin or silicone, black<br>Diaphragm- Stainless Steel 304 |
| <b>Gasket</b>                       | Gasket (Included) 0.125" thick, 60 Durometer Neoprene<br>ASTM B117 Certified - Withstands exposure to salt spray for 300 hours<br>IP 68 Certified - Withstands water submergence and dust exposure               |
| <b>Construction Materials</b>       | Humidity- 95% relative humidity at +40_C continuously for 100 hours.<br>Vibration- Withstands vibration between 0 and 55 Hz. on all axes.<br>10 years under normal operating conditions.                         |
| <b>Life Expectancy</b>              | For a period of two years from the date of manufacture under normal operating conditions.                                                                                                                        |
| <b>Warranty</b>                     | This product is not intended as a life safety device.                                                                                                                                                            |
| <b>Notes</b>                        |                                                                                                                                                                                                                  |
| <b>Terms and Conditions of Sale</b> | <a href="#">Link here</a>                                                                                                                                                                                        |

More Information

 [UL Recognized](#)

 [RoHS Compliant](#)



TOLERANCES ARE  $\pm 0.03\text{in.}$  [ $\pm 0.76\text{mm}$ ] UNLESS OTHERWISE SPECIFIED

Tone Chart

Ap

| IN3 | IN2 | IN1 | Sound | Rate | Frequency |
|-----|-----|-----|-------|------|-----------|
| 0   | 0   | 0   | Off   | X    | X         |

Power Source

|   |   |   |          |       |                |
|---|---|---|----------|-------|----------------|
| 0 | 0 | 1 | Constant | X     | 1800 Hz        |
| 0 | 1 | 0 | Beep     | 2 Hz  | 1800 Hz        |
| 0 | 1 | 1 | Siren    | 3 Hz  | 1600 - 2000 Hz |
| 1 | 0 | 0 | Warble   | 2 Hz  | 1700 - 1800 Hz |
| 1 | 0 | 1 | Chime    | 1 Hz  | 1800 Hz        |
| 1 | 1 | 0 | Whoop    | 3 Hz  | 1600 - 2000 Hz |
| 1 | 1 | 1 | Ringer   | 10 Hz | 1700 - 1800 Hz |

