

## M-80/M-100 Series

M-80XB(F)




## Specifications

|                                   |                                                        |
|-----------------------------------|--------------------------------------------------------|
| <b>Mounting</b>                   | PC Mount                                               |
| <b>Operating Mode</b>             | Extra Loud Fast Beep Tone                              |
| <b>Operating Voltage</b>          | 5-15 Vdc                                               |
| <b>Operating Frequency</b>        | 2900±250 Hz                                            |
| <b>Typical Operating Current</b>  | 10 mA at 5 Vdc<br>50 mA at 15 Vdc                      |
| <b>Termination</b>                | PC Pins                                                |
| <b>Operating Temperature</b>      | -20_C to +65_C                                         |
| <b>Storage Temperature</b>        | -40_C to +85_C                                         |
| <b>Surge Voltage</b>              | 20% over maximum rated voltage for less than 5 minutes |
| <b>Reverse Voltage Protection</b> | To the maximum operating voltage                       |
| <b>Notes</b>                      | This product is not intended as a life safety device.  |

**Terms and Conditions of Sale** [Link here](#)

□



More Information




[UL Recognized](#)



RoHS Compliant

Dimensions



TOLE RANCES ARE ±0.03in [±0.76mm] UNLESS OTHERWISE SPECIFIED