

[AudioLarm II Series](#)

LB-07-530-S(S)



[More Information](#)

## Dimensions

## Specifications

|                                     |                                                                                                                                                                                                                                                                                        |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Mounting</b>                     | Panel Mount                                                                                                                                                                                                                                                                            |
| <b>Operating Mode</b>               | Low Output Slow Beep Tone                                                                                                                                                                                                                                                              |
| <b>Operating Voltage</b>            | 5-30 Vdc                                                                                                                                                                                                                                                                               |
| <b>Operating Frequency</b>          | 2900±250 Hz                                                                                                                                                                                                                                                                            |
| <b>Typical Operating Current</b>    | 2 mA at 5 Vdc<br>20 mA at 30 Vdc                                                                                                                                                                                                                                                       |
| <b>Typical Sound Pressure</b>       | 80 ±5 dB(A) at 5 Vdc at 24 inches (61 cm), at 25°C<br>85 ±5 dB(A) at 30 Vdc at 24 inches (61 cm), at 25°C                                                                                                                                                                              |
| <b>Termination</b>                  | Quick Connect Blades with Screws                                                                                                                                                                                                                                                       |
| <b>Termination Strength</b>         | Pull test with a maximum of 22 pounds (10 kg) load                                                                                                                                                                                                                                     |
| <b>Operating Temperature</b>        | -20_C to +65_C                                                                                                                                                                                                                                                                         |
| <b>Storage Temperature</b>          | -40_C to +85_C                                                                                                                                                                                                                                                                         |
| <b>Surge Voltage</b>                | 20% over maximum rated voltage for less than 5 minutes                                                                                                                                                                                                                                 |
| <b>Reverse Voltage Protection</b>   | To the maximum operating voltage                                                                                                                                                                                                                                                       |
| <b>Construction Materials</b>       | Case- Plastic _NORYL_ N-190, Flame Retardant UL 94-VO, Black<br>Internal Circuit- Audio-oscillator and piezoelectric driver<br>Potting- 2 parts epoxy resin or silicone, black<br>Diaphragm- Stainless Steel 313                                                                       |
| <b>Gasket</b>                       | Gasket (sold separately) 0.062" thick, 60 Durometer Neoprene                                                                                                                                                                                                                           |
| <b>Construction Materials</b>       | ASTM B117 Certified - Withstands exposure to salt spray for 300 hours<br>IP 68 Certified - Withstands water submergence and dust exposure<br>Humidity- 95% relative humidity at +40_C continuously for 100 hours.<br>Vibration- Withstands vibration between 0 and 55 Hz. on all axes. |
| <b>Life Expectancy</b>              | 10 years under normal operating conditions.                                                                                                                                                                                                                                            |
| <b>Warranty</b>                     | For a period of two years from the date of manufacture under normal operating conditions.                                                                                                                                                                                              |
| <b>Notes</b>                        | This product is not intended as a life safety device.                                                                                                                                                                                                                                  |
| <b>Terms and Conditions of Sale</b> | <a href="#">Link here</a>                                                                                                                                                                                                                                                              |

2 SCREWS  
#6-32 x 1/4"  
PHN SLOT SS

1.00in  
[ 25.4mm ]

2 SCREWS  
#6-32 x 1/4"  
PHN SLOT SS

1.00in  
[ 25.4mm ]

Technical drawing of a mechanical assembly showing dimensions for a spring and a plate. The dimensions are as follows:

- Spring diameter: 0.43 in [10.9 mm]
- Plate thickness: 0.50 in [12.8 mm]
- Spring length: 0.46 in [11.7 mm]
- Spring height: 1.11 in [28.3 mm]

Technical drawing of a mechanical assembly showing dimensions for a spring and a plate. The dimensions are as follows:

- Spring diameter: 0.43 in [10.9 mm]
- Plate thickness: 0.50 in [12.8 mm]
- Spring length: 0.46 in [11.7 mm]
- Spring height: 1.11 in [28.3 mm]

STAINLESS STEEL REEL SCREWS  
6 X 32, 0.25 LONG  
(5.4)

0.032 (0.81)  
0.312 (7.9)  
0.312 (7.9)  
0.250 (6.4)  
0.188 (4.8)  
5/32 BREAD

STAINLESS STEEL REEL SCREWS  
6 X 32, 0.25 LONG  
(5.4)

0.032 (0.81)  
0.312 (7.9)  
0.312 (7.9)  
0.250 (6.4)  
0.188 (4.8)  
5/32 BREAD