

[Accessories Series](#)

10 Pack - Turbo Volume Control - Black 61880KIT


**Specifications**

|                                     |                                                                                                                                                                                                     |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Operating Mode</b>               |                                                                                                                                                                                                     |
| <b>Operating Voltage</b>            | 0-0                                                                                                                                                                                                 |
| <b>Operating Temperature</b>        | -20_C to +65_C                                                                                                                                                                                      |
| <b>Storage Temperature</b>          | -40_C to +85_C                                                                                                                                                                                      |
| <b>Surge Voltage</b>                | 20% over maximum rated voltage for less than 5 minutes                                                                                                                                              |
| <b>Reverse Voltage Protection</b>   | To the maximum operating voltage                                                                                                                                                                    |
| <b>Construction Materials</b>       | Plastic _NORYL_ N-190, Flame Retardant UL 94-VO, Black<br>ASTM B117 Certified - Withstands exposure to salt spray for 300 hours<br>IP 68 Certified - Withstands water submergence and dust exposure |
| <b>Construction Materials</b>       | Humidity- 95% relative humidity at +40_C continuously for 100 hours.<br>Vibration- Withstands vibration between 0 and 55 Hz. on all axes.                                                           |
| <b>Life Expectancy</b>              | 10 years under normal operating conditions.                                                                                                                                                         |
| <b>Warranty</b>                     | For a period of two years from the date of manufacture under normal operating conditions.                                                                                                           |
| <b>Notes</b>                        | This product is not intended as a life safety device.                                                                                                                                               |
| <b>Terms and Conditions of Sale</b> | <a href="#">Link here</a>                                                                                                                                                                           |

More Information



RoHS RoHS Compliant