



***Pushlok***



Dimensions


More Information




Specifications

|                              |                                                                                                                                                                                                                                                                                        |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mounting                     | Panel Mount with PushLok Technology                                                                                                                                                                                                                                                    |
| Operating Mode               | Extra Loud Whoop Tone                                                                                                                                                                                                                                                                  |
| Operating Voltage            | 5-15 Vdc                                                                                                                                                                                                                                                                               |
| Operating Frequency          | 2900±250 Hz                                                                                                                                                                                                                                                                            |
| Typical Operating Current    | 5 mA at 5 Vdc<br>25 mA at 15 Vdc                                                                                                                                                                                                                                                       |
| Typical Sound Pressure       | 85 ±5 dB(A) at 5 Vdc at 24 inches (61 cm), at 25°C<br>103 ±5 dB(A) at 15 Vdc at 24 inches (61 cm), at 25°C                                                                                                                                                                             |
| Termination                  | Quick Connect Blades                                                                                                                                                                                                                                                                   |
| Termination Strength         | Pull test with a maximum of 22 pounds (10 kg) load                                                                                                                                                                                                                                     |
| Operating Temperature        | -20_C to +65_C                                                                                                                                                                                                                                                                         |
| Storage Temperature          | -40_C to +85_C                                                                                                                                                                                                                                                                         |
| Surge Voltage                | 20% over maximum rated voltage for less than 5 minutes                                                                                                                                                                                                                                 |
| Reverse Voltage Protection   | To the maximum operating voltage                                                                                                                                                                                                                                                       |
| Construction Materials       | Case- Plastic _NORYL_ N-190, Flame Retardant UL 94-VO, Black<br>Internal Circuit- Audio-oscillator and piezoelectric driver<br>Potting- 2 parts epoxy resin or silicone, black<br>Diaphragm- Stainless Steel 304                                                                       |
| Gasket                       | Gasket (Included) 0.125" thick, 60 Durometer Neoprene                                                                                                                                                                                                                                  |
| Construction Materials       | ASTM B117 Certified - Withstands exposure to salt spray for 300 hours<br>IP 68 Certified - Withstands water submergence and dust exposure<br>Humidity- 95% relative humidity at +40_C continuously for 100 hours.<br>Vibration- Withstands vibration between 0 and 55 Hz. on all axes. |
| Life Expectancy              | 10 years under normal operating conditions.                                                                                                                                                                                                                                            |
| Warranty                     | For a period of two years from the date of manufacture under normal operating conditions.                                                                                                                                                                                              |
| Notes                        | This product is not intended as a life safety device.                                                                                                                                                                                                                                  |
| Terms and Conditions of Sale | <a href="#">Link here</a>                                                                                                                                                                                                                                                              |


REAR




GROMMET



SIDE




FRONT



TOLERANCES ARE  $\pm 0.03$  in [ $\pm 0.76$  mm] UNLESS OTHERWISE SPECIFIED

# MOUNTING



## FITS MATERIAL THICKNESS

0.050in [1.3mm] - 0.150in [3.8mm]

