Floyd Bell Inc
SOUND SOLUTIONS

Turbo Light Series
TLH-87G-930-S



More Information


UL Recognized

Rohs Compliant

Specifications

Mounting	Panel Mount
Color	Ultra Bright Green
Operating Mode	
Operating Voltage	9-30 Vdc
Typical Operating Current	110 mA at 9 Vdc 50 mA at 30 Vdc
Typical Brightness	4500 cd/m^2, at 9 Vdc at 25°C 4700 cd/m^2, at 30 Vdc at 25°C
Termination	Quick Connect Blades with Screws
Termination Strength	Pull test with a maximum of 22 pounds (10 kg) load
Operating Temperature	-40_C to +85_C
Storage Temperature	-40_C to +100_C
Surge Voltage	20% over maximum rated voltage for less than 5 minutes
Reverse Voltage Protection	To the maximum operating voltage
Construction Materials	Lens/Case- Green Translucent Polycarbonate 94 VO Potting- 2 parts epoxy resin or silicone, black
Gasket	NEMA 4X Gasket (Included) 0.125" thick, 60 Durometer Neoprene
Construction Materials	ASTM B117 Certified - Withstands exposure to salt spray for 300 hours IP 68 Certified - Withstands water submergence and dust exposure Humidity- 95% relative humidity at +40_C continuously for 100 hours. Vibration- Withstands vibration between 0 and 55 Hz. on all axes.
Life Expectancy	10 years under normal operating conditions.
Warranty	For a period of two years from the date of manufacture under normal operating conditions.
Notes	This product is not intended as a life safety device.
Terms and Conditions of Sale	Link here

Dimensions


REAR
RING
GASKET
SIDE
FRONT
2 SCREWS
#6-32 x 1/4"
PNH SLOT SS
0.70in
[17.8mm]
1.28in
[32.5mm]
0.31in
[7.9mm]
0.49in
[12.4mm]
0.91in
[23.2mm]
0.24in
[6.0mm]
1.06in
[26.8mm]
Ø 1.30in
[33.0mm]
PANEL MOUNTING
1.065in
[27.051mm]
FITS PANELS UP TO
0.50in (12.7mm) THICK
"S" TERMINALS
STAINLESS STEEL SCREWS,
6 X 32 0.25 (6.4) LONG
6/32 THREAD
TOLERANCES ARE ±0.03in (±0.76mm) UNLESS OTHERWISE SPECIFIED