

## Twin Turbo Series TLHB-V88G-930-SF



More Information



## **Specifications**

**Mounting** Panel Mount with Volume Control

Color Green

Operating Mode Fast Beep Tone
Operating Voltage 9-30 Vdc
Operating Frequency 3000±250 Hz
110 mA at 9 Vdc

**Typical Operating Current**110 mA at 9 Vdc
50 mA at 30 Vdc

Typical Sound Pressure  $85 \pm 5 \text{ dB(A)}$  at 9 Vdc at 24 inches (61 cm), at 25°C  $103 \pm 5 \text{ dB(A)}$  at 30 Vdc at 24 inches (61 cm), at 25°C

**Termination** Quick Connect Blades with Screws

**Termination Strength** Pull test with a maximum of 22 pounds (10 kg) load

Operating Temperature -20\_C to +65\_C Storage Temperature -40\_C to +85\_C

**Surge Voltage** 20% over maximum rated voltage for less than 5 minutes

**Reverse Voltage Protection** To the maximum operating voltage

Construction Materials Lens/Case- Green Translucent Polycarbonate 94 VO

Potting- 2 parts epoxy resin or silicone, black

**Gasket** Gasket (Included) 0.125" thick, 60 Durometer Neoprene

ASTM B117 Certified - Withstands exposure to salt spray for 300 hours IP 68 Certified - Withstands water submergence and dust exposure

Construction Materials

Humidity- 95% relative humidity at +40 C continuously for 100 hours.

Vibration- Withstands vibration between 0 and 55 Hz. on all axes.

**Life Expectancy** 10 years under normal operating conditions.

**Warranty** For a period of two years from the date of manufacture under normal operating conditions.

**Notes** This product is not intended as a life safety device.

Terms and Conditions of Sale Link here

## **Dimensions**

