


Turbo Series

TMW-V86-531-Q(S)



More Information

 [UL Recognized](#)

 **RoHS** Compliant

**Specifications**

|                                     |   |
|-------------------------------------|---|
| <b>Mounting</b>                     | Panel Mount with Volume Control   |
| <b>Operating Mode</b>               | Medium Loud Slow Warble Tone  |
| <b>Operating Voltage</b>            | 5-24 Vac/dc   |
| <b>Operating Frequency</b>          | 2900 $\pm$ 250 Hz   |
| <b>Typical Operating Current</b>    | 2 mA at 5 Vac/dc<br>15 mA at 24 Vac/dc  |
| <b>Typical Sound Pressure</b>       | 75 $\pm$ 5 dB(A) at 5 Vac/dc at 24 inches (61 cm), at 25°C<br>95 $\pm$ 5 dB(A) at 24 Vac/dc at 24 inches (61 cm), at 25°C   |
| <b>Termination</b>                  | Quick Connect Blades  |
| <b>Termination Strength</b>         | Pull test with a maximum of 22 pounds (10 kg) load  |
| <b>Operating Temperature</b>        | -20_C to +65_C  |
| <b>Storage Temperature</b>          | -40_C to +85_C  |
| <b>Surge Voltage</b>                | 20% over maximum rated voltage for less than 5 minutes  |
| <b>Reverse Voltage Protection</b>   | To the maximum operating voltage<br>Case- Plastic _NORYL_ N-190, Flame Retardant UL 94-VO, Black<br>Internal Circuit- Audio-oscillator and piezoelectric driver<br>Potting- 2 parts epoxy resin or silicone, black<br>Diaphragm- Stainless Steel 304  |
| <b>Construction Materials</b>       |   |
| <b>Gasket</b>                       | Gasket (Included) 0.125" thick, 60 Durometer Neoprene<br>ASTM B117 Certified - Withstands exposure to salt spray for 300 hours<br>IP 68 Certified - Withstands water submergence and dust exposure<br>Humidity- 95% relative humidity at +40_C continuously for 100 hours.<br>Vibration- Withstands vibration between 0 and 55 Hz. on all axes. |
| <b>Construction Materials</b>       |   |
| <b>Life Expectancy</b>              | 10 years under normal operating conditions.   |
| <b>Warranty</b>                     | For a period of two years from the date of manufacture under normal operating conditions.   |
| <b>Notes</b>                        | This product is not intended as a life safety device.   |
| <b>Terms and Conditions of Sale</b> | <a href="#">Link here</a>   |

□

## Dimensions

### REAR



### RING



### GASKET



### SIDE



### FRONT



### PANEL MOUNTING



FITS PANELS UP TO  
0.50in [12.7mm] THICK

### "Q" TERMINALS



TOLERANCES ARE  $\pm 0.03$ in ( $\pm 0.76$ mm) UNLESS OTHERWISE SPECIFIED